



Fall protection

AN203100ZZ

ENERGY ABSORBING LANYARDS

Compact energy absorbing lanyard made of high impact webbing to reduce the user's draught



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg
- Strap with improved abrasion resistance and certified for use on sharp edges

Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG



Fall protection

AN203100ZZ

ENERGY ABSORBING LANYARDS

Compact energy absorbing lanyard made of high impact webbing to reduce the user's draught

Standards - Details

Technical details

Type of equipment	Energy absorber in lanyard webbing
Composition of the main support	Polyester
Length	1 m
With connector	yes
Color	Orange
Connector (user side)	Screw carabiner, steel, opening 18mm
Ending	2 sewn thimble loops
Connector (structure side)	Screw carabiner
Lifespan from manufacturing	10 years
Weight	0,600 kg
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)



Fall protection

AN203100ZZ

ENERGY ABSORBING LANYARDS

Compact energy absorbing lanyard made of high impact webbing to reduce the user's draught

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
AN203100ZZ	Orange	1 m	AN203100ZZ	3295249264963	13295249264960	5	1	3.9 kg