



Hand protection

TC716

THERMAL WELDING WORKS

Thick, thermal leather glove, ideal for welding work in heavy industry



Specific benefits



Performance

- The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)
- Extra thick and long for extra protection of the entire arm

Applications

- Public works
- Building
- Maintenance
- Automotive
- Temporary work

Certifications and norms



EN 388
3 1 2 2 X

EN 12477
TYPE A



EN 407
4 1 2 X 4 X

Protects against risks



Heat



Hand protection

TC716

THERMAL WELDING WORKS

Thick, thermal leather glove, ideal for welding work in heavy industry

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
2 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997



EN 407

THERMAL RISKS (X = NOT TESTED)
4 [0-4] BURNING BEHAVIOUR
1 [0-4] CONTACT HEAT RESISTANCE
2 [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
4 [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Welding glove
Mechanical glove kind	Cut and sewn
Special gloves kind	Welding
Thickness (mm)	1,2
Arm level protection	Forearm cuff (< 400mm)
Cuff characteristic	Leather cuff
Benefits element	Reach
Color	Grey
Size	9, 10, 11
Type of packaging	Bulk bag of 12

Packaging

Sale unit: Bulk bag of 12
120 pairs /box



Safety gloves

TC716

THERMAL WELDING WORKS

Thick, thermal leather glove, ideal for welding work in heavy industry

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
TC71609	Grey (C079)	09 (T013)	TC716	3295249181000	13295249181007	120	12	29.4 kg	32.0 cm	87.0 cm	32.0 cm
TC71610	Grey (C079)	10 (T015)	TC716	3295249181017	13295249181014	120	12	29.9 kg	32.0 cm	87.0 cm	32.0 cm
TC71611	Grey (C079)	11 (T017)	TC716	3295249181079	13295249181076	120	12	30.3 kg	32.0 cm	87.0 cm	32.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height