



Hand protection

VE713

WORKS IN OILY ENVIRONMENT

Mechanical glove with high abrasion resistance, ideal for aqueous medium



Specific benefits



Durability

· High-quality coating extends the life of the glove and provides excellent protection for the hand



Hygiene

· Nitrile means no risk of allergies for users



Performance

· The nitrile coating gives people working in oily/greasy environments an excellent grip on the objects they handle

Certifications and norms



Applications

- Agriculture
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Automotive
- Mining

Risk Protection



Wearing



Hand protection

VE713

WORKS IN OILY ENVIRONMENT

Mechanical glove with high abrasion resistance, ideal for aqueous medium

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
2 [0-4] TEAR RESISTANCE
1 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Knitted coated glove
Mechanical Glove Type	Tricot
Fiber	Polyamide
Coating Level	3/4 Coating
Coating Material	Nitrile
Coating Finish	Double Layer
Number of Coatings	Double Coated
Gauge	13
Color	Black
Size	7, 8, 9, 10
Type of conditioning	in individual bag

Packaging

Sale unit: in individual bag

240 pairs /box








Safety gloves

VE713

WORKS IN OILY ENVIRONMENT

Mechanical glove with high abrasion resistance, ideal for aqueous medium

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VE71307	Black	07	VE713	3295249103385	13295249103382	240	10	13.1 kg	29.2 cm	61.0 cm	42.0 cm
VE71308	Black	08	VE713	3295249103392	13295249103399	240	10	14.1 kg	29.2 cm	61.8 cm	40.8 cm
VE71309	Black	09	VE713	3295249103408	13295249103405	240	10	15.9 kg	31.4 cm	67.6 cm	41.0 cm
VE71310	Black	10	VE713	3295249103415	13295249103412	240	10	16.6 kg	43.4 cm	66.4 cm	29.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height