



Fall protection

AN245200PRR

ENERGY ABSORBING LANYARDS

Double lanyard with dielectric energy absorber made of elastic webbing, allowing protection against electrical risks



Specific benefits



Comfort

- Elastic webbing lanyard for easy movement and safety



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Certification above maximum rated load 100kg: product certified at 140kg
- Webbing with better abrasion resistance and certified against sharp edges



Ease of Use

- Ergonomic design facilitates user movement
- Automatic carabiners for secure locking and time saving

Applications

- Agriculture
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Oil & Gas (Extraction)

Certifications and norms



EN355
140 KG

Risk Protection



Fall



enjoy safety

Edit 10/08/2026
www.deltaplus-usa.com



Fall protection

AN245200PRR

ENERGY ABSORBING LANYARDS

Double lanyard with dielectric energy absorber made of elastic webbing, allowing protection against electrical risks

Standards - Details

Technical details

Type of equipment	Extensible webbing lanyard
Composition of the main support	Polyester, Steel with plastic overmolded
Length (m)	2
With connector	yes
Color	Black-Red
Connector 1	Small hook made of insulating material, opening 20mm
Ending	2 sewn thimble loops
Connectors (structure side)	2 big hooks made of insulating material, Hook made of insulating material, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,9
Fall arrest work situations	Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616
Dielectric optional test	30 Kv



Fall protection

AN245200PRR

ENERGY ABSORBING LANYARDS

Double lanyard with dielectric energy absorber made of elastic webbing, allowing protection against electrical risks

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN245200PRR	Black-Red (C131)	1.40 → 2 m (T216)	AN245200PRR	3295249202316	13295249202313	5	1	10.994 kg	29.4 cm	45.2 cm	25.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height