



Fall protection

AN213200ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Performance

- Webbing with better abrasion resistance and certified against sharp edges
- Certification above maximum rated load 100kg: product certified at 140kg

Applications

- Public Works
- Finishing Works/Craftsmanship
- Automotive
- Power Energy
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Risk Protection



Fall



enjoy safety

Edit 10/10/2026
www.deltaplus-usa.com



Fall protection

AN213200ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Steel, Polyester
Length (m)	2
With connector	yes
Color	Orange
Connector 1	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connectors (structure side)	2 automatic lock hooks, steel, opening 55mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,6
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	6.5616



Fall protection

AN213200ZDD

能量吸收带

双大钩减震带，有抗高冲击的织带制成，配有两个大开口安全钩，短距离适用

物流信息

产品代码	颜色	尺码	六位码	条形码	箱码			重量			
AN213200ZDD	橙色	2米	AN213200ZDD	3295249265083	13295249265080	5	1	9.47 kg	45.0 cm	29.5 cm	18.0 cm



箱规



最低销售



箱长



箱宽



箱高