



Fall protection

IPN LV130

ANCHORAGE DEVICES

Temporary anchorage device for IPN structures with wheels that allow the anchorage to be slid away



Applications

- Building
- Finishing Works/Craftsmanship
- Maintenance
- Chemical Industry
- Oil & Gas (Extraction)
- Mining

Certifications and norms



EN 795
TYPE B

Risk Protection



Fall



Fall protection

IPN LV130

ANCHORAGE DEVICES

Temporary anchorage device for IPN structures with wheels that allow the anchorage to be slid away

Standards - Details

Technical details

Type of equipment	Interim anchorage device with wheels
Composition of the main support	Aluminum, Steel, Stainless steel, Polyester
Fastening	Zipper fastening
Color	Steel
Weight (kg)	4,251
Use	For beams of width 76 to 255 mm
Fall arrest work situations	Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Long horizontal movement on vertical structure



IPN LV130

DISPOSITIVOS DE ANCLAJE

Protección anticaídas

Dispositivo de anclaje temporal para estructuras IPN con ruedas que permiten deslizar el anclaje

Información logística

Referencia	Color	Tamaño	Descripción	EAN 13	Código caja			Peso			
LV130	Acero	Ajustable	IPN LV130	3295249171360	13295249171367	4	1	17.9 kg	44.0 cm	39.0 cm	39.0 cm



Caja completa



Mín. Vta. (múltiplo)



Box Width



Box Depth



Box Height