



AN211200CDD

ENERGY ABSORBING LANYARDS

Fall protection



Applications

- Building
- Finishing works / Craftsmanship
- Maintenance
- Power Energy
- Storage

Certifications and norms



EN355
100 KG

Protects against risks



Fall



AN211200CDD

ENERGY ABSORBING LANYARDS

Fall protection

Standards - Details

Technical details

Type of equipment	Twisted rope lanyard
Composition of the main support	Steel, Polyamide, Polyester
Length (m)	2
Color	White
Connector (user side)	Screw carabiner, steel, opening 18mm
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Length (ft)	6.5616








AN211200CDD

ENERGY ABSORBING LANYARDS

Fall protection

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN211200CDD	White	2 m	AN211200CDD	3295249183240	13295249183247	5	1	9.9 kg	28.0 cm	44.0 cm	15.0 cm

 Multiple sales

 Minimum sales

 Box Width

 Box Depth

 Box Height